



## **CEE Combination Unit 32A 200/346V-240/415V 3P+N+PE 6 h IP44 Screw Connection**

**Product Code: 406651V**

METECEE - Combination Unit, 32A, 200/346V-240/415V, 3P+N+PE, 6 h, IP44, Colour:Grey, Screw Connection, Contact Material:Brass 16A. Socket Typr: German; sockets connected by cable ,Cable Entry: Front,Bottom,Back Entry, Cable Cross Section: 2,5-6mm<sup>2</sup> ,made

## Technical Information

Version:	
Product Name	Combination Unit
Angle	-
Connection Design	Screw Connection
Technical Characteristics:	
Current (A)	32A
Poles No. (P99)	5P
Voltage (V)	200/346V-240/415V
Voltage EN 60309-2 (V)	400V
Poles No. (P)	3P+N+PE
Protection Degree	IP44
Position Of Earth Contact (h)	6 h
Frequency (Hz)	50~60Hz
Cable Entry	Front, Bottom, Back Entry
Cable Cross Section for Wire Flexible (mm <sup>2</sup> )	2,5-6mm <sup>2</sup>
Cable Cross Section for Wire Solid (mm <sup>2</sup> )	2,5-10mm <sup>2</sup>
Strain Relief (Ncm)	-
Dismantling Length (mm)	50mm
Contact Screws (Ncm)	110Ncm
Stripping Length (mm)	12-14mm
Flange Size Vertical (mm)	-
Flange Size Horizontal (mm)	-
Drill Hole Distance Vertical (mm)	-
Drill Hole Distance Horizontal (mm)	-
Additional Technical Information	with safety socket (Austrian/German standard) - ready wired
Material Properties:	
Colour	Grey
Material of Enclosure	Plastic
Contact Material	Brass
Certificateion:	
Certificates	ÖVE  TSE
Commercial Data:	
Weight/pcs	0.480 kg
Packaging Quantity	5
HS Code	8536.69.90.00.18
Country of Origin	Austria

### METE ENERJİ A.Ş.

#### Address:

10007 Sk. No 34 A.O.S.B 35620 Çiğli, İzmir, Türkiye  
Tel: +90 (232) 376 86 86

© 2020 Mete Energy All Rights Reserved.