

Variable frequency drive, 400 V AC, 3-phase, 150 A, 75 kW, IP55/NEMA 12,  
Radio interference suppression filter, OLED display, DC link choke



Powering Business Worldwide™

**Part no.** DA1-34150FB-B55C

**169401**

**EL Number**

**4137323**

**(Norway)**

Product name	Eaton DA1 Variable frequency drive
Part no.	DA1-34150FB-B55C
EAN	4015081658428
Product Length/Depth	313.5 millimetre
Product height	865 millimetre
Product width	330 millimetre
Product weight	50 kilogram
Certifications	<ul style="list-style-type: none"> <li>UL</li> <li>IEC/EN61800-5</li> <li>Certified by UL for use in Canada</li> <li>UL Category Control No.: NMMS, NMMS7</li> <li>CE</li> <li>UL 508C</li> <li>IEC/EN 61800-3</li> <li>CUL</li> <li>Specification for general requirements: IEC/EN 61800-2</li> <li>Safety: EN 61800-5-1: 2003</li> <li>RoHS, ISO 9001</li> <li>UkrSEPRO</li> <li>UL report applies to both US and Canada</li> <li>UL File No.: E172143</li> <li>CSA-C22.2 No. 14</li> <li>RCM</li> <li>DNV</li> <li>EAC</li> <li>IEC/EN61800-3</li> </ul>
Product Tradename	DA1
Product Type	Variable frequency drive
Product Sub Type	None
Catalog Notes	The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.
Cable length	<ul style="list-style-type: none"> <li>100 m, screened, maximum permissible, Motor feeder</li> <li>300 m, unscreened, with motor choke, maximum permissible, Motor feeder</li> <li>C3 ≤ 25 m, Radio interference level, maximum motor cable length</li> <li>150 m, unscreened, maximum permissible, Motor feeder</li> <li>C2 ≤ 5 m, Radio interference level, maximum motor cable length</li> <li>200 m, screened, with motor choke, maximum permissible, Motor feeder</li> </ul>
Communication interface	<ul style="list-style-type: none"> <li>CANopen®, built in</li> <li>DeviceNet, optional</li> <li>Modbus RTU, built in</li> <li>OP-Bus (RS485), built in</li> <li>PROFIBUS, optional</li> <li>Modbus-TCP, optional</li> <li>Ethernet IP, optional</li> <li>EtherCAT, optional</li> <li>SmartWire-DT, optional</li> <li>PROFINET, optional</li> </ul>
Connection to SmartWire-DT	<ul style="list-style-type: none"> <li>In conjunction with DX-NET-SWD1 SmartWire DT module</li> <li>Yes</li> </ul>
Degree of protection	<ul style="list-style-type: none"> <li>NEMA 12</li> <li>IP55</li> </ul>
Electromagnetic compatibility	1st and 2nd environments (according to EN 61800-3)
Fitted with:	<ul style="list-style-type: none"> <li>DC link choke</li> <li>PC connection</li> <li>Radio interference suppression filter</li> <li>Breaking resistance</li> <li>IGBT inverter</li> <li>Brake chopper</li> <li>Internal DC link</li> <li>OLED display</li> <li>Control unit</li> <li>Additional PCB protection</li> </ul>
Frame size	FS6

Functions		4-quadrant operation possible
Mounting position		Vertical
Product Category		Variable frequency drives
Protection		Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
Protocol		CAN PROFINET IO DeviceNet PROFIBUS MODBUS Other bus systems EtherNet/IP TCP/IP
Safety function/level		STO (Safe Torque Off, SIL2, PLc Cat 2)
Suitable for		Branch circuits, (UL/CSA)
Radio interference class		Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Ambient operating temperature - min		-10 °C
Altitude		Max. 1000 m Above 1000 m with 1 % derating per 100 m Max. 4000 m
Ambient operating temperature - max		40 °C
Ambient operating temperature at 150% overload - min		-10 °C
Ambient operating temperature at 150% overload - max		40 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		60 °C
Climatic proofing		< 95 average relative humidity (RH), no condensation, no corrosion
Efficiency		97.9 % ( $\eta$ )
Heat dissipation at current/speed		1200 W at 100% current and 0% speed 1530 W at 100% current and 50% speed 1650 W at 100% current and 90% speed 570 W at 25% current and 0% speed 570 W at 25% current and 50% speed 700 W at 50% current and 0% speed 840 W at 50% current and 90% speed 860 W at 50% current and 50% speed
Input current ILN at 150% overload		164.7 A
Leakage current at ground IPE - max		2.68 mA
Mains switch-on frequency		Maximum of one time every 30 seconds
Mains voltage - min		380 V
Mains voltage - max		480 V
Operating mode		U/f control Speed control with slip compensation Sensorless vector control (SLV) Optional: Vector control with feedback (CLV)
Output frequency - min		0 Hz
Output frequency - max		500 Hz
Output voltage (U2)		400 V AC, 3-phase 480 V AC, 3-phase
Overload current IL at 150% overload		225 A
Rated control supply voltage		10 V DC (Us, max. 10 mA)
Rated frequency - min		48 Hz
Rated frequency - max		62 Hz
Rated operational current (Ie) at 150% overload		150 A
Rated operational power at 380/400 V, 50 Hz, 3-phase		75 kW
Rated operational voltage		480 V AC, 3-phase 400 V AC, 3-phase
Resolution		0.1 Hz (Frequency resolution, setpoint value)
Short-circuit protection rating		200 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
Starting current - max		200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section

Supply frequency		50/60 Hz
Switching frequency		4 kHz, 4 - 12 kHz adjustable (audible), fPWM, Power section, Main circuit
System configuration type		AC supply systems with earthed center point
Voltage rating - max		480 V AC
Assigned motor current IM at 400 V, 50 Hz, 150% overload		134 A
Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload		124 A
Assigned motor power at 460/480 V, 60 Hz, 3-phase		100 HP
Apparent power at 400 V		103.92 kV-A
Apparent power at 480 V		124.71 kV-A
Braking resistance		6 Ω
Braking torque		Max. 30 % MN, Standard - Main circuit Max. 100 % of rated operational current Ie with external braking resistor - Main circuit Max. 100 % of rated operational current Ie, variable, DC - Main circuit
Switch-on threshold for the braking transistor		780 V DC
Number of inputs (analog)		2
Number of inputs (digital)		5
Number of outputs (analog)		2
Number of outputs (digital)		2
Number of relay outputs		2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
Rated control voltage (Uc)		24 V DC (external, max. 100 mA)
Equipment heat dissipation, current-dependent Pvid		1575 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		150 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)		
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter = < 1 kV (ec@ss10.0.1-27-02-31-01 [AKE177014])		
Mains voltage	V	380 - 480
Mains frequency		50/60 Hz
Number of phases input		3
Number of phases output		3
Max. output frequency	Hz	500
Max. output voltage	V	500
Nominal output current I2N	A	150
Max. output at quadratic load at rated output voltage	kW	75
Max. output at linear load at rated output voltage	kW	75
Relative symmetric net frequency tolerance	%	10
Relative symmetric net voltage tolerance	%	10
Number of analogue outputs		2
Number of analogue inputs		2
Number of digital outputs		2
Number of digital inputs		5
With control element		Yes
Application in industrial area permitted		Yes
Application in domestic- and commercial area permitted		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		Yes
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		Yes
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for BACnet		No
Supporting protocol for other bus systems		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0
Number of HW-interfaces other		0
With optical interface		No
With PC connection		Yes

Integrated breaking resistance			Yes
4-quadrant operation possible			Yes
Type of converter			U converter
Degree of protection (IP)			IP55
Degree of protection (NEMA)			12
Height		mm	865
Width		mm	330
Depth		mm	313.5